

HMI DIGITAL 575 W

HMI DIGITAL | Lámparas de halogenuros metálicos, un casquillo



Áreas de aplicación

- Studio
- Stage
- TV

Beneficios del producto

- Suited for both analog and digital film production
- Robust stems, resulting in less breakage during transport
- Round moly-foil construction that evenly distributes heat and current extends for lamp longevity (6,000-18,000 W)
- Splash-proof carrying case is re-usable and allows lamps to be transported safely (6,000-18,000 W)

Características del producto

- High CRI of >90
- UV-Stop (UVS)
- Color temperature of 6,000 K (daylight)
- Extremely bright light of up to 100 lumens/watt
- Capacidad de nuevo arranque en caliente

Datos técnicos

Datos eléctricos

Potencia nominal	57500 W
Tensión nominal	940 V
Corriente nominal	61 A

Datos Fotométricos

Flujo luminoso nominal	49000 lm
Temperatura de color	6400 K
Índice de reproducción cromática Ra	90

Dimensiones y peso

Diámetro	3000 mm
Largo	1450 mm

Duración de vida

Duración	1000 h
----------	--------

Datos adicionales del producto

Casquillo (denominación estándar)	G22
-----------------------------------	-----

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899984134
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Hoja de datos de producto

Instrucciones de seguridad

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Código del producto	Descripción del producto	Unidad de embalaje (Piezas/unidad)	Dimensiones (largo x ancho x alto)	Volúmen	Peso bruto
4052899984134	HMI DIGITAL 575 W	Estuche de cartón 1	57 mm x 57 mm x 173 mm	0.56 dm ³	163.00 g
4052899984172	HMI DIGITAL 575 W	Embalaje de envío 10	295 mm x 125 mm x 190 mm	7.01 dm ³	1734.00 g

El código del producto mencionado describe la unidad más pequeña de la cantidad que se puede pedir. Una unidad de envío puede contener uno o más productos individuales. Al cursar un pedido, introduzca la cantidad de la unidad de envío o su múltiple.

Aviso

Sujeto a cambios sin aviso. Excepto errores y omisiones. Asegúrese de utilizar la emisión más reciente.